## HAMILT®N

## 5 μL Microliter Syringe Model 75 N, Cemented Needle, 26s gauge, 2 in, point style 2

Specification Sheet (Part/REF # 87900)

The 700 series syringe is the original hand-fitted Hamilton syringe. This series of syringes is ideal for dispensing volumes from 0.5  $\mu$ L up to 500  $\mu$ L. A variety of different terminations and needle options are available in this series.

the warman was a survive the

## **Product Specifications**

Volume	5 μL
Syringe Type	Microliter
Syringe Series	700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	26s gauge
Point Style	2
Needle Length	2 inch (51 mm)
Fluid Path	SST, borosilicate glass
Autoclavable	No
Gas Sterilizable	Yes
Pressure	2000 psig (137.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C/50°F
Barrel Inner Diameter	0.014 inches (0.343 mm)

HAMILT®N

Visit **www.hamiltoncompany.com/support** to find a representative in your area or call us: US: +1-775-525-3000 EU: +40-356-635-055

## HAMILT@N

products/syringes/87900

Barrel Outer Diameter	0.260 inches (6.60 mm)	
Needle Inner Diameter	0.005 inches (0.13 mm)	
Needle Outer Diameter	0.019 inches (0.483 mm)	
Std Needle Dead Volume	0.64 µL	
Sales Quantity	1 syringe per pack	
Specifications are subject to change without notice https://www.hamiltoncompany.com/laboratory-		Spec. Version B

HAMILT®N

Visit <u>www.hamiltoncompany.com/support</u> to find a representative in your area or call us: US: +1-775-525-3000 EU: +40-356-635-055