

# 100 $\mu$ L Microliter Syringe Model 710 N, Cemented Needle, 22s gauge, 2 in, point style 2

Specification Sheet (Part/REF # 80600)



Split/splitless injection consists of a heated chamber with a glass liner into which the sample is injected through the septum. A microsyringe is used to inject the sample through a rubber septum into a flash vaporizer chamber at the head of the column.

## Product Specifications

<b>Volume</b>	100 $\mu$ L
<b>Syringe Type</b>	Microliter
<b>Syringe Series</b>	700
<b>Termination</b>	Cemented Needle (N)
<b>Needle</b>	Cemented Needle
<b>Gauge</b>	22s gauge
<b>Point Style</b>	2
<b>Needle Length</b>	2 inch (51 mm)
<b>Fluid Path</b>	SST, borosilicate glass
<b>Autoclavable</b>	No
<b>Gas Sterilizable</b>	Yes
<b>Pressure</b>	2000 psig (137.9 bar)
<b>Maximum Temperature</b>	50°C / 122°F
<b>Minimum Temperature</b>	10°C / 50°F
<b>Barrel Inner Diameter</b>	0.061 inches (1.46 mm)

Barrel Outer Diameter	0.305 inches (7.75 mm)
Needle Inner Diameter	0.0059 inches (0.15 mm)
Needle Outer Diameter	0.0283 inches (0.72 mm)
Std Needle Dead Volume	1.13 µL
Sales Quantity	1 syringe per pack

Specifications are subject to change without notice  
<https://www.hamiltoncompany.com/laboratory-products/syringes/80600>

Spec. Version B